



Modular PDA Packs in Memory

Simplify data collection with a pocket-sized, memory-rich PDA that scans barcodes, reads RFID tags, and offers two keypad options.

SCAN ME



Loaded with memory—128 MB SDRAM and 1 GB internal flash memory standard. Expandable with a user-accessible SD card slot.

Small, rugged form factor—6.1 × 3.2 × 1.2 in. (155 × 82 × 31 mm) and weighs 13.4 oz. (380 g).

Windows® CE 5.0—offers quick start-up with virtually no time wasted waiting for boot-up.

Accurate barcode scanning—1D laser or 1D/2D imager for barcode scanning.

Two-year standard warranty—among the longest in the industry.

Modular design provides RFID flexibility—a high frequency (HF) or ultra-high frequency (UHF) RFID reader. Configure it for your current needs and easily upgrade it later as needed.

Independently lab-tested ruggedness—sealed to IP65 and meets MIL-STD-810F requirements.

Wireless communication—GPRS/GSM 3G, WLAN with a Summit 802.11 b/g radio, Bluetooth®, and GPS.

Indoor/outdoor LCD touchscreen—adjustable LED backlighting and crisp 256K color on a 3.5-inch touchscreen.

Accessories



Single Dock



4-Slot Charging Dock



Belt Holster



RFID Module



4-Slot Charger

Core System	
Operating System	Windows® CE 5.0 Professional Windows® Embedded Handheld 6.5
Processor	Marvell® PXA270 520 MHz
Memory	128 MB SDRAM 1 GB Flash SD card slot (supports up to 16 GB)
Display	
	3.5-inch QVGA (240 × 320) transfective TFT color LCD with LED backlight 4-wire resistive touchscreen Passive stylus or finger operation
Keypad & Buttons	
Common features	Backlit 3 barcode scanning triggers 4 dedicated programmable keys Navigation keys
M2010	12-key numeric keypad
M2020	26-key alpha-numeric keypad
Communications	
WLAN	Integrated Summit 802.11 b/g
WWAN	Optional GPRS/GSM 3G module
GPS	Integrated SiRFstar III GPS
Bluetooth®	Integrated Bluetooth® v2.0 + EDR Class II
Infrared	Integrated IrDA 1.2 compliant
Input/Output	
Power jack	5 VDC input
LIF Connector	RS-232 USB host/client 5 VDC/100 mA power in
Barcode Scanning	
Short range	1D laser 1D/2D imager
RFID Modules	
High frequency (HF)	Protocol: ISO 159693, ISO 14443-A/B 13.56 MHz
Ultra-high frequency (UHF)	Protocol: EPC Class I Gen 2 ISO 18000-6C Chipset: Impinj R2000 United States: 902–928 MHz Europe: 865–868 MHz China: 920–925 MHz Japan: 952–954 MHz NCC: 922–928 MHz
Expansion Slots	
	SD card slot (supports up to 16 GB) Optional SIM slot for GPRS/GSM 3G

Audio	
	Mono speaker 2.5 mm stereo headset (audio in/out) Internal microphone
Software	
	ActiveSync, FTP client/server, IE 6.0, Viewers for Microsoft® Office and PDF files, Inbox, Windows Media Player, Remote Desktop, Terminal Services, Voice Recorder, Summit WLAN utility, Backup and Restore, Barcode Scanner Utility, (software update from SD card)
Power	
Standard battery	Li-ion battery pack, 3.7 VDC, 2200 mAh
High-capacity battery	Li-ion battery pack 3.7 VDC, 4000 mAh
Backup	Rechargeable internal backup battery
Power Adapter	Power adapter, 100–240 VAC, 50/60 Hz input, 5 VDC/2.6 A output
Dimensions	
	6.1 (L) × 3.2 (W) × 1.2 (H) in. [155 × 82 × 31 mm] 13.4 oz. [380 g] (with standard battery pack)
Regulatory	
	FCC 47 CFG Class 1 Part 15 (US) ETSI EN 302 208-1 (V1.1.1/EU) RoHS (DoC) WEEE (DoC)
Safety	UL/cUL, LVD, CB
Environment	
Operating temperature	-4 to +122 °F [-20 to +50 °C]
Charging temperature	32 to +104 °F [0 to +40 °C]
Storage temperature	-22 to +158 °F [-30 to +70 °C]
Drop	Multiple 5-foot (1.5-meter) drops to concrete
Tumble	2000 1-meter tumbles at room temperature
ESD	15 kV air discharge, 8 kV direct discharge
Sealing	IP65 certified
Humidity	5%–95%, non-condensing

Feature Configurations

Barcode Scanning Options (select one)	WLAN	Bluetooth	WWAN	GPS
1D laser scanner (short range)	•	•	•	•
1D/2D imager (short range)	•	•	•	•
RFID Options (select one)	WLAN	Bluetooth	WWAN	GPS
High frequency	•	•	•	•
Ultra-high frequency	•	•	•	•
Identity Management Options	WLAN	Bluetooth	WWAN	GPS
Identity Management Module	•	•	•	•



United States
tel +1 (855) 327-8324
fax +1 (480) 705-4216
7450 South Priest Drive
Tempe, AZ 85283, USA

Canada
tel +1 (800) 363-1993
fax +1 (418) 681-0799
875, boul. Charest O. Bureau 200
Québec (QC) Canada G1N 2C9

Europe, Middle East, Africa
tel +44 (0) 1235 462130
fax +44 (0) 1235 462131
25 Nuffield Way
Abingdon, England OX 14 1RL